

Docket No. AUS920010758US1

**CLAIMS:**

What is claimed is:

1. A method in a data processing system for  
5 automatically tracking insertions of integrated circuit  
devices into a receptacle device, said method comprising  
the steps of:  
automatically detecting, utilizing said data  
processing system, an insertion of an integrated circuit  
10 device into said receptacle device; and  
in response to a detection of an insertion of said  
integrated circuit device into said receptacle device,  
automatically incrementing an insertion count associated  
with said integrated circuit device, wherein said  
15 insertion count is used to track insertions of said  
integrated circuit device into said receptacle device.
2. The method according to claim 1, further comprising  
the step of automatically detecting, utilizing said data  
20 processing system, an insertion of an MCM assembly into a  
planar.
3. The method according to claim 2, further comprising  
the step of automatically detecting, utilizing said data  
25 processing system, an insertion of an interposer into a  
planar.
4. The method according to claim 1, further comprising  
the step of automatically detecting, utilizing said data  
30 processing system, an insertion of an MCM into an  
interposer.

Docket No. AUS920010758US1

5. The method according to claim 1, further comprising the step of automatically detecting, utilizing said data processing system, an insertion of an IC into a printed circuit board.

5

6. The method according to claim 1, further comprising the steps of:

providing vital product data for said IC device;

establishing an insertion count field within said

10 vital product; and

storing within said insertion count field a current number of times said IC device has been inserted into said receptacle.

15 7. The method according to claim 1, wherein the step of automatically detecting an insertion of an integrated circuit device into said receptacle device further comprises the steps of:

20 first detecting an absence of an integrated circuit device from said receptacle; and

next detecting a presence of an integrated circuit device in said receptacle.

25 8. The method according to claim 7, further comprising the steps of:

first detecting an absence of a presence detect pin in said receptacle; and

next detecting a presence of a presence detect pin in said receptacle.

30

9. The method according to claim 8, further comprising the step of in response to a detection of a presence

Docket No. AUS920010758US1

detect pin in said receptacle, incrementing an insertion count field associated with an integrated circuit device inserted into said receptacle.

- 5 10. The method according to claim 1, further comprising the steps of:

determining whether said insertion count exceeds an insertion threshold; and

- 10 in response to a determination that said insertion count exceeds said insertion threshold, reporting an error and a location of said integrated circuit device.

11. The method according to claim 10, further comprising the step of returning said integrated circuit device.

15

12. A data processing system for automatically tracking insertions of integrated circuit devices into a receptacle device, comprising:

- 20 said data processing system for automatically detecting an insertion of an integrated circuit device into said receptacle device; and

- 25 in response to a detection of an insertion of said integrated circuit device into said receptacle device, said data processing system for automatically incrementing an insertion count associated with said integrated circuit device, wherein said insertion count is used to track insertions of said integrated circuit device into said receptacle device.

- 30 13. The system according to claim 12, further comprising said data processing system for automatically detecting an insertion of an MCM assembly into a planar.

Docket No. AUS920010758US1

14. The system according to claim 13, further comprising said data processing system for automatically detecting an insertion of an interposer into a planar.

5 15. The system according to claim 12, further comprising said data processing system for automatically detecting an insertion of an MCM into an interposer.

10 16. The system according to claim 12, further comprising said data processing system for automatically detecting an insertion of an IC into a printed circuit board.

17. The system according to claim 12, further comprising:

15        vital product data provided for said IC device;  
         an insertion count field established within said  
vital product; and  
         said data processing system for storing within said  
insertion count field a current number of times said IC  
20 device has been inserted into said receptacle.

18. The system according to claim 12, wherein said data processing system for automatically detecting an insertion of an integrated circuit device into said  
25 receptacle device further comprises:

         said data processing system for first detecting an absence of an integrated circuit device from said receptacle; and

30        said data processing system for next detecting a presence of an integrated circuit device in said receptacle.

Docket No. AUS920010758US1

19. The system according to claim 18, further comprising:

said data processing system for first detecting an absence of a presence detect pin in said receptacle; and

5       said data processing system for next detecting a presence of a presence detect pin in said receptacle.

20. The system according to claim 19, further comprising in response to a detection of a presence detect pin in  
10       said receptacle, said data processing system for incrementing an insertion count field associated with an integrated circuit device inserted into said receptacle.

21. The system according to claim 12, further  
15       comprising:

said data processing system for determining whether said insertion count exceeds an insertion threshold; and

in response to a determination that said insertion count exceeds said insertion threshold, said data  
20       processing system for reporting an error and a location of said integrated circuit device.

22. The system according to claim 21, further comprising said integrated circuit device being returned.

25

23. A computer program product in a data processing system for automatically tracking insertions of integrated circuit devices into a receptacle device, said computer program product comprising:

30       instruction means for automatically detecting, utilizing said data processing system, an insertion of an integrated circuit device into said receptacle device;

2025 RELEASE UNDER E.O. 14176

Docket No. AUS920010758US1

and

in response to a detection of an insertion of said integrated circuit device into said receptacle device, instruction means for automatically incrementing an insertion count associated with said integrated circuit device, wherein said insertion count is used to track insertions of said integrated circuit device into said receptacle device.

24. The product according to claim 23, further comprising instruction means for automatically detecting, utilizing said data processing system, an insertion of an MCM assembly into a planar.
25. The product according to claim 24, further comprising instruction means for automatically detecting, utilizing said data processing system, an insertion of an interposer into a planar.
26. The product according to claim 23, further comprising instruction means for automatically detecting, utilizing said data processing system, an insertion of an MCM into an interposer.
27. The product according to claim 23, further comprising instruction means for automatically detecting, utilizing said data processing system, an insertion of an IC into a printed circuit board.
28. The product according to claim 23, further comprising:

Docket No. AUS920010758US1

instruction means for providing vital product data for said IC device;

instruction means for establishing an insertion count field within said vital product; and

- 5 instruction means for storing within said insertion count field a current number of times said IC device has been inserted into said receptacle.

29. The product according to claim 23, wherein said  
10 instruction means for automatically detecting an insertion of an integrated circuit device into said receptacle device further comprises:

instruction means for first detecting an absence of an integrated circuit device from said receptacle; and

- 15 instruction means for next detecting a presence of an integrated circuit device in said receptacle.

30. The product according to claim 29, further comprising:

- 20 instruction means for first detecting an absence of a presence detect pin in said receptacle; and

instruction means for next detecting a presence of a presence detect pin in said receptacle.

- 25 31. The product according to claim 30, further comprising in response to a detection of a presence detect pin in said receptacle, instruction means for incrementing an insertion count field associated with an integrated circuit device inserted into said receptacle.

30

32. The product according to claim 23, further comprising:

Docket No. AUS920010758US1

instruction means for determining whether said  
insertion count exceeds an insertion threshold; and

in response to a determination that said insertion  
count exceeds said insertion threshold, instruction means  
5 for reporting an error and a location of said integrated  
circuit device.

099744-100404